QTY.	PRODUCT	NEXT ASSY. DWG.	NO.	DESCRIPTION OF CHANGE	SCO#	DATE	BY
			0	NEW ISSUE		01/23/17	DSE
			2				
			3				
			4				
2. Dime only 8 purpo	iudes mounting have ensions are for inchange are not require	ick Gasket  48-  ardware aformation purposes d for inspection	plea · sup s re	Filter Element Type 18.0 PTF 24, MERV fits, aprox 24 mm Pleat Height, Hard PU toports and gasket.  **Commended that the compressed air for at an operating range of 4 to 5 bar, \$  **All Public	op and bot the cleanir bar being	tom, Aluminion	um y⊂le
	$\ni$			Ø25 600 —			50
ITEN#		ED		DESCRIPTION		-	
	TIONS ±1/64	ESS OTHERWISE SPECIFI DECIMALS .X ±.	1 .>	THIS DOCUMENT IS THE PROPERTY OF SHALL NOT BE COPIED, REPRODUCED,	RICHARDSON USED IN THE	ELECTRONICS MANUFACTURE	, LTD. AND E OR SALE
ANGL	ES ±1/2° DO NOT SCALI	.xx ±,0: E DRAWING	ι .Χ)	(xx ±.005 of apparatus or disclosed to other section of the control of the contro			
DRAWN	DSE			DUST COLLEC			_ • • • • •
ENG. MGR.		ENG. CHKD.		REPLACES T			
ENG. MGR.		PRODN. APPD.				T/IN	
MAT'L				0380	101		
MAT'L. SPEC. NO	<u> </u>	I		RFT75	7/10	CHAI	NGE
FINISH	_	PROD.			/ / I U		$\overline{}$

-Z